

COHILLS PRO SERIES[®] EZ-STAMP

Cohills Pro Series[®] EZ-Stamp Stampable Overlay is a premixed blend of special materials that, when properly mixed with water and placed on an existing concrete substrate forms a thin, cementitious overlay or coating suitable for stamping or texturing, similar to a standard concrete pour. It can be used to restore or revive, old worn out concrete. When used on properly prepared concrete surfaces that are primed with Cohills Pro Series[®] Dura Prime. Cohills Pro Series[®] EZ-Stamp will permanently bond, and with a psi stronger than most concrete it will withstand years of wear.

COVERAGE: 1-50 lb bag will typically cover 22 ft² @ ¼" thick 11 ft² @ ½" thick

Directions for use:

SURFACE PREPARATION: Surface must be clean and free of all oils, grease, paint, sealers, or anything that would interfere with proper bonding. All crack repairs, scarifying and shot blasting should have taken place prior to pressure washing. All existing control and expansion joints must be honored as they will telegraph through the overlay. Pressure-wash all dust and laitents from the surface to ensure a clean surface. Achieve a SSD (Saturated Surface Dry) condition with water immediately before the installation to cool the concrete and decrease rapid hydration. No standing water should be present upon application. Before overlay placement, prime the surface generously with Cohills Pro Series[®] EZ-Bond Polymer using either a short napped roller or weed sprayer. One generous coat is all that is required. Make sure that no puddles are present.

MIXING: Measure 4 to 4.5 quarts water per bag and add to the desired mixing container. Actual liquid requirements will vary depending upon climate and weather conditions. Add dry mix. Using a drill powered mixer with a paddle blade, (or for larger jobs use a large mortar mixer) mix all material at medium speed until completely lump free. Mix should be of a consistency so that it can be placed easily with a gauged rake. It is much easier however, to add C-Series Colorants instead of a Ez-Pack.

PLACEMENT: Pour the material directly onto the surface immediately after mixing. Using a gauge rake set to the desired depth, rake the material out, but leave a furrow line of material to mix in with the following batch. Wear spiked overlay shoes to allow walking in the wet material. Immediately after each batch has been raked, use a trowel, float, or squeegee to remove the gauge rake lines. When the material leaves an indent but doesn't transfer to a finger when touched, it is ready for stamping or texturing. If Powdered Antiquing Release is to be used, apply just prior to stamping. If Cohills Pro Series[®] Liquid Release is to be used, do not apply release until immediately before the stamp is to be applied. Apply a generous amount to the stampable surface and the stamp mat as well. Do not allow puddles to form.

STAMPING/TEXTURING: Use any Cohills Pro Series[®] texturing mat or texture skin that does not exceed 1/2 the depth of the applied thickness. Unlike concrete, Cohills Pro Series[®] EZ-Stamp stampable Overlay does not require heavy pressure or extreme tamping. Apply only enough even pressure to seat the mat and provide an impression. Allow 36 hours before foot traffic. Re-cut all control joints to the original substrate to avoid cracking. Allow the overlay to cure for a minimum of 7 days, protect the surface with Cohills Pro Series[®] Clear Seal HS.

LIMITED WARRANTY: This product is not intended for public use and is intended for use by licensed contractors and installers, experienced and trained in the use of these products. Cohills Building Specialties, Inc. warrants its products to be free of manufacturing defects, to be of good quality, and that they will meet Cohills Building Specialties, Inc. current published physical properties when applied in accordance with Cohills Building Specialties, Inc. written directions and tested in accordance with ACI, ASTM and Cohills Building Specialties, Inc. Standards. Product proved to be defective will be replaced. User assumes all liability for the acceptability, use, safety and fitness for purpose of this product and Cohills Building Specialties, Inc. shall not be liable for damages of any sort, including remote or consequential damages, resulting from any claimed breach of any warranty, whether expressed or implied, from any other cause whatsoever. There are no other warranties by Cohills Building Specialties, Inc. of any nature whatsoever, expressed or implied, including any warranty of merchantability or fitness for a particular purpose in connection with this product including wear or service life. Cohills Building Specialties, Inc. will not be responsible for use of this product in a manner that infringes on any patent held by others.

Cohills Building Specialties, Inc.
3825 East Anne Street
Phoenix, Az. 85040
Telephone: 602-266-0462
Customer Service: 877-709-2220
www.cohills.com

Cohills Pro Series[®] **EZ-Stamp** available through: